

LIGHTNING CUT™

SUCCESS AT LIGHTNING SPEED

SUCCESS AT LIGHTNING SPEED

The **Lightning Cut** from **Salem Fabrication Supplies** is a premium line of high-speed, self-dressing diamond core drills. This line is part of our **Storm Series** of products and provides very smooth finish quality –even at higher feed-rates than those offered by industry standard products. Our **Lightning Cut** core drills are available in both 95 mm and 75 mm overall lengths.



Lightning Cut – Premium Self-Dressing Diamond Core Drills – 95 mm OAL

Salem's premium **95 mm OAL Lightning Cut** core drills are designed for rigorous use on **Forvet™ machines**. Ask about our premium 75 mm OAL Lightning Cut core drills for CNC machines!

BENEFITS

- Self-sharpening –no dressing is required
- High feed rates with very smooth finish quality
- Stainless steel body for extra durability
- Operator friendly –easy to use
- Readily available –short lead times on custom sizes
- Reduced production costs with:
 - Longer life and faster drilling speed
 - Consistent performance throughout drill life

USAGE INSTRUCTIONS

- No initial dressing is needed –ready to perform right out of the box
- Capable of feeds of up to 1.8 mm/sec
 - Run at 1.4 mm/sec for cleaner cutting

Lightning Cut – Standard Parameters (95 mm OAL)

Ø	RPM	Feed Rate	Item #
6.35 mm	4,300	1.0 - 1.8 mm/s	DD6.35LCLP
9.5 mm	2,900	1.0 - 1.8 mm/s	DD9.5LCLP
10 mm	2,700	1.0 - 1.8 mm/s	DD10LCLP
11 mm	2,500	1.0 - 1.8 mm/s	DD11LCLP
12.7 mm	2,200	1.0 - 1.8 mm/s	DD12.7LCLP
14.28 mm	2,000	1.0 - 1.8 mm/s	DD14.28LCLP
15.9 mm	1,750	1.0 - 1.8 mm/s	DD15.9LCLP
19.05 mm	1,450	1.0 - 1.8 mm/s	DD19.05LCLP
22.3 mm	1,250	1.0 - 1.8 mm/s	DD22.3LCLP
25.4 mm	1,150	1.0 - 1.8 mm/s	DD25.4LCLP

The standard working parameters listed on this chart is only for **Lightning Cut** core drills and may need adjustment depending on the working conditions.

Higher feeds are possible, but may require an incremental increase of RPM.

CONTACT SALEM TODAY! LEARN MORE ABOUT OUR THUNDER CUT LINE!



800.234.1982 | info@salemftg.com | www.SalemFTG.com

Salem Fabrication Supplies is a division of Salem Fabrication Technologies Group, Inc. | We Are 100% Employee Owned

Diamond Tooling

Core Drills | Countersinks | Cup Wheels | Peripheral Wheels | Routers



Window Glass Products

Approved Cutting Fluids | Dual-Belt Seamers
Edge Deletion Wheels | Material Handling
Sanding Belts and Discs



Abrasives

Loose Abrasives | Sanding Belts
Sanding Discs | Wheel Dressing



Polishing Products

Cerium Impregnated Wheels | Cerium Oxide | Cup Polishing Wheels
Edge Deletion Wheels | Felt Wheels | Peripheral Polishing Wheels



Coolants & Additives

Biocide | Coolants | Cutting Fluids
Defoamer | Flocculant




Material Handling

Carts, Racks & Tables | Cranes
Dollies | Vacuum Hand Cups
Vacuum Lifters, Rotators & Tilters



Other Equipment

Dual-Belt Seamers | Markers



Glazing Supplies & More

Adhesives | Cleaners | Cork & Felt Tabs
Corner Protectors | EVA Laminating Film
Gloves | Hand Cutters | Protective Coatings
Razor Blades | Sealants | Tape | And More



Explore our full line of
machinery & equipment at:
HHHGlassEquipment.com

HHH Equipment Resources is a
division of **Salem Fabrication
Technologies Group, Inc.**

CONTACT SALEM TODAY! LEARN MORE ABOUT OUR FULL LINE OF TOOLING & SUPPLIES!

SALEM

FABRICATION SUPPLIES



SHOP ONLINE

800.234.1982 | info@salemftg.com | www.SalemFTG.com

Salem Fabrication Supplies is a division of Salem Fabrication Technologies Group, Inc. | We Are 100% Employee Owned